

# Epic Hyperspace Integration Quick Reference Card

## PowerScribe® 360 | Reporting (version 2.0 and higher) Optional Feature

**NOTE:** Nuance employees are not authorized to adjust or configure the settings on a customer's PACS. The customer, or the customer's PACS representative, must make any necessary changes to the PACS configuration or settings.

### Feature Overview

**NOTE:** This integration operates in **Slave Mode only**.

#### Slave Mode

- Single login/logout
- Mark exam as dictated/read
- Can be installed on the same PC as the PACS/RIS




#### Multiple Sites and Multiple Integrations




- If the system has multiple *sites* and the integration type is master, duplicate the master mode integration under each site. If the integration type is slave do not set up duplicate integrations under each site. Set up all slave integrations under the primary site (first site created). When a user logs in, no matter what site they are working under, the system will read the slave integrations created under the primary site and confirm the workstation is set up with the correct directory structures.
- If there are multiple *integrations* on a system, and more than one uses file drop integration such as XML, you will need to ensure that each file drop integration drops files into, or reads files from, separate sub folders under **c:\Nuance** on the client workstation.

For example, an organization using both GE and Hologic might consider using the following paths:

- C:\Nuance\GE\
- C:\Nuance\Hologic\

### Site PACS Settings

1. Go to **Setup > Sites > PACS** section.
2. Click the **Edit**  icon for the PACS you want to configure as Slave (or click the **Add**  icon to create a new PACS entry).
3. From the **Type** drop-down list, select **PowerScribe XML**.
4. In the **Name** field, type **PowerScribe XML**. (The **Description** field is optional.)
5. In the **Mode** section, select **Slave**.
6. In the **Slave** text field, enter  
**c:\Nuance\study.xml; c:\Nuance\status.xml;MultiAccSeparator=\\;multisite=all**  
Optional edit for multisite:
  - **thissite** - Only the configured site will be searched.
  - **selected** - Search will be based on the value selected in the site drop-down box in *PowerScribe 360 | Reporting*.
7. Click the **Save**  icon. Your entry should look like the example illustration below.

PACS:	Type	Name	Description	Mode
 	PowerScribe XML	PowerScribe XML		<b>Slave:</b> c:\nuance\study.xml;c:\nuance\status.xml;password=hox;base64=False
				

Page 1

This page intentionally left blank.