

Fuji Synapse Integration Quick Reference Card

PowerScribe® 360 | Reporting Desktop Client Integration

NOTE: Nuance employees are not authorized to adjust or configure the settings on a customer's PACS. The customer, or the customer's PACS representative, must make any necessary changes to the PACS configuration or settings.

Feature Overview

In **Master** mode:

- Mark exam as dictated/read
- Launch PACS images using PowerScribe 360 | Reporting work list
- Launch PowerScribe 360 | Reporting report using PACS work list
- Can be installed on same PC as PACS/RIS

In **Slave** mode:

- Application launch
- Single login/logout
- Mark exam as dictated/read




Multiple Sites and Multiple Integrations


- If the system has multiple *sites* and the integration type is master, duplicate the master mode integration under each site. If the integration type is slave do not set up duplicate integrations under each site. Set up all slave integrations under the primary site (first site created). When a user logs in, no matter what site they are working under, the system will read the slave integrations created under the primary site and confirm the workstation is set up with the correct directory structures.
- If there are multiple *integrations* on a system, and more than one uses file drop integration such as XML, you will need to ensure that each file drop integration drops files into, or reads files from, separate sub folders under **c:\Nuance** on the client workstation.

For example, an organization using both GE and Hologic might consider using the following paths:

- C:\Nuance\GE\
- C:\Nuance\Hologic\

Site PACS Settings: Master

1. Go to **Setup > Sites > PACS** section.
2. Click the **Edit**  icon for the PACS you want to configure as Master (or click the **Add**  icon to create a new PACS entry).
3. From the **Type** drop-down list, select **RadWhere URL/XML**.
4. In the **Name** field, type **Fuji**. (The **Description** field is optional.)
5. In the **Mode** field, select **Master**.
6. In the **Master** text field, enter the URL, which contains {accession}, {mrn}, {username}, or {password} as substitution variables. The site PACS administrator might have the information required. If not, consult with Fuji Support for specifics.
Example: **http://PACS1/images?accession={accession}**
7. Click the **Save**  icon. Your entry should look like the example illustration below.

PACS:		Type	Name	Description	Mode
	 	RadWhere URL/XML	Fuji		Master: http://PACS1/images?accession={accession}
					




Page 1




Fuji Synapse Integration Quick Reference Card

PowerScribe® 360 | Reporting Desktop Client Integration

Site PACS Settings: Master (continued)




Alternative Master Configuration to pass XML context

1. Go to **Setup > Sites > PACS** section.
2. Click the **Edit**  icon for the PACS you want to configure as Master (or click the **Add**  icon to create a new PACS entry).
3. From the **Type** drop-down list, select **PowerScribe XML**.
4. In the **Name** field, type **PowerScribe XML**. (The **Description** field is optional.)
5. In the **Mode** field, select **Master**.
6. In the **Master** text field, enter **c:\nuance\status.xml**.
7. Click the **Save**  icon. Your entry should look like the example illustration below.

PACS:		Type	Name	Description	Mode
		PowerScribe XML	PowerScribe XML		Master: c:\Nuance\Status.xml
					

Page 1

Site PACS Settings: Slave

1. Go to **Setup > Sites > PACS** section.
2. Click the **Edit**  icon for the PACS you want to configure as Slave (or click the **Add**  icon to create a new PACS entry).
3. From the **Type** drop-down list, select **PowerScribe XML**.
4. In the **Name** field, type **Fuji**. (The **Description** field is optional.)
5. In the **Mode** section, select **Slave**.
6. In the **Slave** text field, enter **c:\nuance\study.xml;c:\nuance\status.xml**.
7. Click the **Save**  icon. Your entry should look like the example illustration below.

PACS:		Type	Name	Description	Mode
		PowerScribe XML	Fuji		Slave: c:\Nuance\order.xml;c:\nuance\status.xml
					

Page 1